

Name	Size	Material	Form	Unevenness compens	Acoustic insulation IS	Load resistance CS	Thermal conduction TR	Floor heating
Underlay for panels 3 mm	50 x 100 cm	extruded polystyrene XPS	board	≥ 1,5 mm	≥ 19 dB	≥ 65 kPa	0,032 m ² K/W	
Underlay for panels 5 mm	50 x 100 cm	extruded polystyrene XPS	board	≥ 4 mm	≥ 19 dB	≥ 65 kPa	0,032 m ² K/W	
Underlay for panels 5 mm puzzle	50 x 100 cm	extruded polystyrene XPS	puzzle	≥ 4 mm	≥ 19 dB	≥ 65 kPa	0,032 m ² K/W	
Underlay for panels 2 mm	1,1 x 22,7 m	extruded polystyrene XPS	roll	≥ 1,5 mm	≥ 19 dB	≥ 35 kPa	0,032 m ² K/W	
Underlay for panels 3 mm openwork	50 x 100 cm	extruded polystyrene XPS	board	≥ 2 mm	≥ 19 dB	≥ 30 kPa	0,032 m ² K/W	●
Underlay for panels 2 mm HDPE	1 x 15 m	closed cell foam HDPE	board	≥ 1,5 mm	= 19 dB	= 60 kPa	0,036 m ² K/W	●