



## Motivo decorative wall

Technical Data Sheet



Profile Type	Motivo
Material	PVC-U
Width	250 / 330 mm
Lenght	2,65 m
Weight	0,405 kg/m
Thinkness	7,9 – 8,2 mm
Joint	Smooth ,tongue-and-groove joint
Accessories	PVC, 3m i 6m
Packing	330 mm – 3 szt. 250 mm – 4 szt.
Tools	Conventional joiner tools.
Storage	The Motivo decorative wall should be stored indoors, on a dry, flat and stable place the substrate, ensuring no direct contact with the ground, in a horizontal position, at a temperature not higher than 60 ° C without exposing them to direct action sunlight.
Fastening	a) For wooden battens, batten distance - 40cm b) For glue for a smooth, non-flaking substrate
Important installation information	- the product can be installed in wet rooms (kitchen, bathroom), provided that it is sealed with silicone - do not install in places exposed to an open flame (gas stove) - assembly with glue - smooth, non-shedding substrate, glue based on hybrid polymer
Maintenance	The Motivo decorative wall should be cleaned with water and a light detergent and a cloth. Don't leave detergent on the surface, rinse thoroughly after cleaning. The Motivo decorative wall should not be cleaned sharp and coarse cloths, sponges and brushes. Intensive scrubbing and the use of strong agents cleaning agents or leaving the detergents without rinsing may damage the panel surface or discolor the material. Do not use solvents or acids for cleaning and principles and measures based on these ingredients.
Environmental characteristics	The product is 100% recyclable

Essential characteristics	Essential characteristics	Assessment methods
Impact resistance	Not less than 3J (23,03)	EN 13245-2:2008/AC:2009
Release of hazardous substances	A+	
Reaction to fire	C-s3;d0	
Fastening strength	See: assembly instructions	



QUICK TO INSTALL



LOW WEIGHT



WATERPROOF



EASY TO KEEP CLEAN



GLUED TO THE WALL

